

**PATENT ABSTRACTS OF JAPAN**

(11)Publication number : 08-127772

(43)Date of publication of application : 21.05.1996

(51)Int.Cl.

C09K 11/64

C09K 11/64

(21)Application number : 06-268463

(71)Applicant : NEMOTO TOKUSHU KAGAKU KK

(22)Date of filing : 01.11.1994

(72)Inventor : MURAYAMA YOSHIHIKO

TAKEUCHI NOBUYOSHI

AOKI YASUMITSU

MATSUZAWA TAKASHI

**(54) PHOTOSTIMULABLE PHOSPHOR****(57)Abstract:**

**PURPOSE:** To obtain a photostimulable phosphor which shows long-term after glow, is chemically stable, and has excellent long-term light resistance.

**CONSTITUTION:** The phosphor comprises as a base crystal a compound represented by the formula  $M1-XAl_2O_4-X$ , wherein M is at least one metal selected among calcium, strontium, and barium and  $-0.33 \leq X \leq 0.60$  (provided that X is not 0). According to need, magnesium can be added to M. Europium can be added as an activator. A coactivator can also be added.

**LEGAL STATUS**

[Date of request for examination] 25.10.2001

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 3456553

[Date of registration] 01.08.2003

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]


[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

**GB1190520**

**Patent number:** GB1190520  
**Publication date:** 1970-05-06  
**Inventor:**  
**Applicant:**  
**Classification:**  
**- International:** C09K  
**- european:** C09K11/02B; C09K11/77N6  
**Application number:** GBD1190520 19681119  
**Priority number(s):** NL19670015823 19671122

**Also published as:**

 NL6715823 (A)  
FR1592842 (A)  
ES360446 (A)  
DE1806751 (A1)  
CH485318 (A)

more &gt;&gt;

**Report a data error he****Abstract of GB1190520**

1,190,520. Luminescent materials. PHILIPS ELECTRONIC & ASSOCIATED INDUSTRIES Ltd. 19 Nov 1968 [22 Nov., 1967], No. 54876/68. Heading C4S. An alkaline earth aluminate phosphor activated by divalent Eu is defined by the formula  $Ba_x Sr_y Ca_z Eu_p - Al_{12} O_{19}$ , wherein  $x+y+z+p=1$ . and  $0 \leq p \leq 0.001$ , preferably  $0 \leq p \leq 0.001$  and  $x \leq 0.7$ . A specific phosphor disclosed is  $Ba_{(1-p)} Eu_p Al_{12} O_{19}$ . In preparation, the mix is heated at 1100 to 1250 C. for 2 hours, cooled, ground, reheated at 1300 to 1500 C. for 2 hrs. in a  $N_2 - H_2$  atmosphere. The phosphor, with emissions of from 380 to 440 nm. wavelength, may be used in HP and LPMV lamps for photo-chemical document copying processes, a reflecting layer of titanium dioxide in the anathese rather than rutile modification being included between the phosphor and its support. Intensities at high temperatures (e.g. 250 C.) are considered.

---

Data supplied from the esp@cenet database - Worldwide